


# THE TALLMAX

## FRAMED 144 LAYOUT MODULE



**144 LAYOUT**  
MULTICRYSTALLINE MODULE

**340-355W**  
POWER OUTPUT RANGE

**17.7%**  
MAXIMUM EFFICIENCY

**0~+5W**  
POSITIVE POWER TOLERANCE

Founded in 1997, Trina Solar is the world's leading total solution provider for solar energy. With local presence around the globe, Trina Solar is able to provide exceptional service to each customer in each market and deliver our innovative, reliable products with the backing of Trina as a strong, bankable brand. Trina Solar now distributes its PV products to over 100 countries all over the world. We are committed to building strategic, mutually beneficial collaborations with installers, developers, distributors and other partners in driving smart energy together.

### Comprehensive Products and System Certificates

IEC61215/IEC61730/UL1703/IEC61701/IEC62716  
 ISO 9001: Quality Management System  
 ISO 14001: Environmental Management System  
 ISO14064: Greenhouse Gases Emissions Verification  
 OHSAS 18001: Occupation Health and Safety Management System



PRODUCTS | POWER RANGE  
 TSM-PE15H | 340-355W



### High power

- Up to 355W front power and 17.7% module efficiency with half-cut technology bringing more BOS savings
- Lower resistance of half-cut ensure high power



### High reliability

- Ensured PID resistance through cell process and module material control
- Resistant to salt, acid and ammonia
- Mechanical performance: Up to 5400 Pa positive load and 2400 Pa negative load




### High energy generation


- Excellent IAM and low light performance validated by 3rd party with cell process and module material optimization
- Lower NMOT bring more energy leading to lower LCOE
- Better anti-shading performance and lower operating temperature

### PERFORMANCE WARRANTY


10 Year Product Warranty · 25 Year Power Warranty




### DIMENSIONS OF PV MODULE(mm)




Front View




Back View



### I-V CURVES OF PV MODULE(345W)



### P-V CURVES OF PV MODULE(345W)



### ELECTRICAL DATA (STC)

Peak Power Watts- $P_{MAX}$ (Wp)*	340	345	350	355
Power Output Tolerance- $P_{MAX}$ (W)	0 ~ +5			
Maximum Power Voltage- $V_{MPP}$ (V)	37.5	37.7	37.9	38.1
Maximum Power Current- $I_{MPP}$ (A)	9.06	9.15	9.23	9.32
Open Circuit Voltage- $V_{OC}$ (V)	46.2	46.4	46.7	47.0
Short Circuit Current- $I_{SC}$ (A)	9.53	9.62	9.71	9.81
Module Efficiency $\eta_m$ (%)	16.9	17.2	17.4	17.7

STC: Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass AM1.5.  
\*Measuring tolerance: ±3%.

### ELECTRICAL DATA (NMOT)

Maximum Power- $P_{MAX}$ (Wp)	257	261	265	269
Maximum Power Voltage- $V_{MPP}$ (V)	35.5	35.7	35.9	36.1
Maximum Power Current- $I_{MPP}$ (A)	7.24	7.31	7.37	7.45
Open Circuit Voltage- $V_{OC}$ (V)	43.5	43.7	44.0	44.2
Short Circuit Current- $I_{SC}$ (A)	7.69	7.76	7.83	7.91

NMOT: Irradiance at 800W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1m/s.

### MECHANICAL DATA

Solar Cells	Multicrystalline
Cell Orientation	144 cells (6 × 24)
Module Dimensions	2015 × 996 × 35 mm (79.33×39.21×1.38 inches)
Weight	22.0 kg ( 48.5 lb)
Glass	3.2 mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant Material	EVA
Backsheet	White
Frame	35 mm ( 1.38 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm <sup>2</sup> (0.006 inches <sup>2</sup> ), Portrait: N 140mm/P 285mm(5.51/11.22inches) Landscape: N 1400 mm /P 1400 mm (55.12/55.12 inches)
Connector	MC4 EVO2 / TS4*

\*Please refer to regional datasheet for specified connector.

### TEMPERATURE RATINGS

NMOT (Nominal Module Operating Temperature)	41°C (±3°C)
Temperature Coefficient of $P_{MAX}$	- 0.38%/°C
Temperature Coefficient of $V_{OC}$	- 0.31%/°C
Temperature Coefficient of $I_{SC}$	0.05%/°C

(Do not connect Fuse in Combiner Box with two or more strings in parallel connection)

### MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC) 1500V DC (UL)
Max Series Fuse Rating	20A

### WARRANTY

10 year Product Workmanship Warranty
25 year Power Warranty

(Please refer to product warranty for details)

### PACKAGING CONFIGURATION

Modules per box: 30 pieces
Modules per 40' container: 660 pieces